

# ROLLS

## HDC39 HDMI Converter


### HDC39 HDMI To Audio Converter

- Converts HDMI to stereo RCA line level.
- Converts HDMI to 5.1 SPDIF.
- Power supply is included.



**ROLLS**

Rolls Corporation  
Salt Lake City, UT  
8/17



### Quick Start Guide

Thank you for your purchase of the HDC39 HDMI to audio converter.

This versatile unit will take an HDMI input, and convert it to Stereo left and right RCA's, convert HDMI to SPDIF in 5.1.

#### INSPECTION

##### 1. Unpack and Inspect the HDC39 package

Your HDC39 was carefully packed at the factory in a protective carton. Nonetheless, be sure to examine the unit and the carton for any signs of damage that may have occurred during shipping. If obvious physical damage is noticed, contact the carrier immediately to make a damage claim.

2. For warranty information, visit our web site at [www.rolls.com](http://www.rolls.com), and click on the REGISTER YOUR WARRANTY HERE text. If you are unable to register online, please complete the Warranty Registration Card and return it to the factory.

#### SPECIFICATIONS

HDMI resolution:	24/50/60fs 1080p/1080i/720p/576p/1576i 480p/480i
Video color format:	24 bit, 30 bit, 36 bit
Max Bandwidth:	225 MHz
Max baud rate:	6.75 Gbps
Input/Output TMDS signal:	0.5-1.5 Volts p-p(TTL)
Input/Output DDC signal:	5 Volts p-p(TTL)
Max working current:	500mA
Power adapter:	5VDC @ 1A TIP NEGATIVE
Dimensions:	84.5 X 61 X 21 (mm)
Weight:	135g

#### DESCRIPTION/OPERATION:

HDMI IN: For connection of the HDMI input that you want to convert.

HDMI OUT: HDMI output.

SPDIF: SPDIF output.

RCA: Left and Right RCA outputs when selector switch is in the PASS or CH2 setting.

VDC: DC power jack connector ( 5VDC @ 1A TIP NEGATIVE ). To connect the HDC39 to the included power supply.

As described above the HDC39 will convert from HDMI to HDMI, SPDIF or Stereo RCA's. When selecting the "PASS" on the selector switch the HDMI OUT and RCA outputs will have content. When the selector switch is in the "5.1" section only the HDMI and SPDIF will have signal present. When the selector switch is in the "CH2" setting only signal will be present on the RCA and HDMI output jacks.